



إيطالكو ميدل إيست م.م.ح  
ITALCO MIDDLE EAST F.Z.E

## MANUAL TRIMMING MACHINE FOR STRAIGHT AND SHAPED PANELS SCM GROUP MINIMAX MOD. T20



### TECHNICAL DATA

Panel thickness	mm	14-80
Max. edge thickness	mm	4
Minimum panel width	mm	100
Minimum panel length	mm	200
Minimum internal radius	mm	25
Installed motor power	kW	1,5
Variable cutters speed	Rpm	9.000 – 15.000
Exhaust outlets diameter	mm	2x80
Overall dimensions	mm	1000x800x1400(h)

ITALCO MIDDLE EAST F.Z.E. Licence No. 148505, Dubai - U.A.E

Tel.: +971 (0)4 3478209 ■ P.O. Box 263848 ■ Email : info@italcome.com ■ Web : www.italcome.com

Warehouse No. JA5-JA6-HA7, Blue Shed, Jebel Ali Free Zone North  
Tax Registration Number : 100260132400003

مستودع JA5-JA6-HA7، السقيفة الزرقاء، المنطقة الحرة في جبل علي الشمالية، دبي، الإمارات العربية المتحدة  
رقم التسجيل الضريبي : 100260132400003

ITALCO MIDDLE EAST FZE has been duly formed as a Free Zone Establishment with limited liability pursuant to Law No. 9 of 1992 and implementing regulations issued thereunder by the Jebel Ali Free Zone

إيطالكو ميدل إيست م م ح قد تم تأسيسها كمؤسسة منطقتة حرة ذات مسؤولية محدودة طبقاً للقانون رقم 9 لسنة 1992 وللأنظمة المنبثقة للقانون الصادر عن المنطقة الحرة لجبل علي



**STANDARD EQUIPMENTS:**

- **High rigidity and stability steel Monoblock base**
- **Scratch phenolic multilayer worktable with modular holes**  
complete with adjustable and rotating supports (no. 20 standard supports)
- **Trimming group:**  
complete with:
  - two 0,55 kW motors with support carriages running on ground guides
  - manual device for moving the two motors apart vertically to facilitate the insertion of curved panels
  - horizontal adjustment of the upper motor to enable the trimming of panel with chamfered edge
  - vertical adjustment of the upper motor to enable adjustment to match panel thickness
  - 200 Hz inverter, complete with electronic brake
  - integrated exhaust outlets to ensure a clean worktable always without hampering the machining
- **Copying devices:**  
complete with:
  - vertical-scratch copiers kit to ensure optimum machine operation. Two pair of copiers: one with three bearings for straight panels, and the other one with single large dimensions bearing for curved and shaped panels
  - simple and immediate positioning of tools with reference to the cutting point, by means of pivoting rings with decimal indication (Scm patent)
  - front interchangeable rotating copying devices kit with hardened, ground chromed contact surfaces. 5 different copiers are supplied as standard for an easy and rapid machine set up. (R2 or R3 or chamfered or straight or tilted edge). Scm exclusive system
- **Pair of multifunction diamond cutters R=2mm**
- **62.13.93 Front extension for the support of large dimensions panels**

